

NE
NE
Please insert the heading, SUMMARY OF THE INVENTION, before the paragraph beginning on page 1, line 32.

NE
NE
Please replace the paragraph beginning on page 2, line 1, with the following rewritten paragraph:

Q2
This problem is solved remarkably well by means of a volumetric operating system according to the present invention, for vehicle lifts. Further advantageous characteristics of the said system are indicated hereinafter.

NE
Please insert the heading, BRIEF DESCRIPTION OF THE DRAWINGS, before the paragraph beginning on page 2, line 6.

NE
Please insert the heading, DETAILED DESCRIPTION, before the paragraph beginning on page 2, line 17.

IN THE CLAIMS:

NE
Please cancel claim 1.

NE
Please add new claims 2-4.

Q3
2. (New) A vehicle lift comprising:
a plurality of vehicle lifting runways;
a volumetric operating system including an operating fluid supply, a pair of main cylinders and a pair of secondary cylinders that cooperate to move the vehicle lifting runways, wherein
the pair of main cylinders receive operating fluid directly from the operating fluid supply, and
each of the secondary cylinders receive operating fluid indirectly from an operating fluid outlet of a respective one of the main cylinders.

3. (NEW) A vehicle lift as in claim 2 wherein at least one of the said main cylinders, and at least one of the secondary cylinders are associated with each runway.